

COBHAM

Ultra-compact comms-on-the-move Inmarsat BGAN terminal

February 2020 Draft Product Sheet



EXPLORER 323

Ultra-compact comms-on-the-move BGAN terminal

Compact voice and broadband solution

EXPLORER 323 is an ultra compact BGAN terminal for voice and data communication on-the-move, a perfect match for our Cobham PRISM PTT+ solution.

The one-piece system consists of a combined tranceiver and switched beam antenna with integrated wifi.

Whether you're engaged in humanitarian operations, cargo or rail transportation, telemedicine or emergency services, you need easy deployable communication equipment you can always rely on - regardless of time or place.



Simply place the terminal on the roof - it is easily mounted with optional magnetic mounts - and connect your phone to the EXPLORER app or log onto the wireless network with your PC to turn the vehicle into a mobile communication hub.

No moving parts

The beam switching antenna is ultra compact and lightweight (just 3.9 kg / 8.5 lbs), ideal for vehicles or trains on-the-move. It is designed for robust and durable use with no moving parts.

No roaming

BGAN offers mobile broadband connectivity wherever you go at fixed pricing with no roaming fees. With the EXPLORER 323 you know your cost of communication regardless of the number of borders you cross.

COBHAM

First of its kind

As a vehicular terminal, EXPLORER 323 is the first terminal to obtain both Inmarsat Class 12 Type Approval and BGAN M2M Certification, enabling it to operate with traditional BGAN and BGAN M2M SIM cards.

General

User Interface:	Status LED
	Web interface
	Factory default reset
Languages:	UK, FR, DE, ES, RU, JP, CN, PT
Approvals:	CE, GMPCS, FCC, IC, RTM
	Inmarsat Class 12 and
	Inmarcat M2M Type Approval

User Interface:	Status LED
	Web interface
	Factory default reset
Languages:	UK, FR, DE, ES, RU, JP, CN, PT
Approvals:	CE, GMPCS, FCC, IC, RTM
	Inmarsat Class 12 and
	Inmarsat M2M Type Approval

Specifications

Dimensions and Weight

Height: 9.7 cm / 3.82 inches (incl. mounts) Width: Ø321 cm / Ø12.7 inches Weight: 3.9 kg / 8.5 lbs

Global Services

4 kbps AMBE+2 Voice:

Standard IP (Rx/Tx): Up to 384 / 225 kbps (>20° elevation)

Up to 270 / 158 kbps (>5° elevation)

Streaming IP: 32, 64 kbps (>20° elevation)

32 kbps (>5° elevation) 160 characters

On-The-Move Communication IP Data and Voice:

Services supported at vehicle

speeds up to 200 km/h (125 mph)

Inmarsat frequencies: 1518.0 - 1525.0 MHz (Rx) (EMEA)

1525.0 - 1559.0 MHz (Rx) 1626.5 - 1660.5 MHz (Tx) 1668.0 - 1675.0 MHz (Tx) (EMEA)

Interfaces

1 x WLAN interface

Standard: 802.11 b/g

1 x LAN interface

Data rate: 10/100 Mbps

Combined DC power and Ethernet connector

Combined connector providing DC power input, ignition and Ethernet connectivity

Hybrid cable, wires: Power 2, Ignition 1, Ethernet 4 + 1 (shield)

BGAN SIM-Card slot

Environmental conditions

Temperature

-25 to +55°C / -13 to 131°F Operational: Survival: -40 to +80°C / -40 to 176°F -40 to +85°C / -40 to 185°F Storage:

Relative humidity: 95% non-condensing at +40°C / +104°F

Water and dust (IP-rating)

Terminal: IP66

Power

DC input range (nom.):	12 - 24VDC
Power (max) @10.5-32V.:	35W

Other features

EXPLORER Connect App

For making telephone calls from your smartphone. Available for Android and iPhone.

Set-up and Router Functionality

Webserver, Built-in NAT Router, Admin control (password protected), DHCP, Network Management, Remote Management, SIP Server, Point-to-Point Protocol over Ethernet (PPPoE)

Package

EXPLORER 323 terminal (combined tranceiver and switched beam antenna). 6m combined DC power and Ethernet cable (open ended), installation guide

Product number

Accessories

403723A-009	Magnetic mount solution
403706A-050	EXPLORER Connection Box
403723A-060	15m cable for 24V DC and Ethernet

For further information please contact:

Cobham SATCOM Lundtoftegaardsvej 93 D DK-2800 Kgs. Lyngby Denmark

Tel: +45 3955 8800

